

Low Price, High Quality. We reduced the product price. But, we did not renounce to quality!



### My50 E/B scrubbing machine.

# AFFORDABLE,

# because it does not need skilled operators for driving!





USER FRIENDLY DESIGN No operator training

You can start working with just 3 quick and simple operations!



Fill in the solution tank and switch on the machine!

Lower the squeegee...

... and start to work!

### My50 E/B scrubbing machine.

## AFFORDABLE, because it offers more autonomy.



#### Autonomy up to 3 hours with 1 full charge





Non-stop work up to 1 hour and 2.000 sq.m with 1 fill of solution



Energy

The FSS (Fimap Solution Saver) system allow to adjust water consumption according to cleaning needs

My50 E/B scrubbing machine.


# AFFORDABLE,

## thanks to the new squeegee in reinforced plastic.



It is safer, because more resistant to impacts and corrosion. Automatic squeegee\* uncoupling when accidentally impacted

\* PATENT PENDING



#### It can be easily cleaned at the end of cleaning operation, even by untrained operators. It is quick to be cleaned!

The easy identification of the parts involved in the daily maintenance (with yellow colour) ensures all parts' check and sanification at the end of work, guaranteeing the maximum efficiency of the machine



Empty and sanitize...





Clean the squeegee!

... recharge! (Battery version)

An on-board charger option makes battery re-charging safe and easy (on request)

Clean the filter!

# Available equipment:

STANDARD EQUIPMENT	My50 E	My50 B		
Water and detergent management				
FSS (Fimap Solution Saver)	•	•		
Eco On/OFF System* - Water filter	optional	optional		
Fast water filling with drip stop	•	•		
Water level indicator	•	•		
Scrubbing performance				
Squeegee with polyurethane	•	•		
rubber bars usable on 4 sides				
Cleaning along walls (right side with 55 cm brush)	•	•		
Operating autonomy				
12 V/102 Ah C20 (2) batteries	-	optional		
12V/75 Ah C20 (2) gel batteries	-	optional		
12 V/120 Ah C20 (2) batteries	-	optional		


STANDARD EQUIPMENT	My50 E	My50 B		
Comfort				
FNC (FimapNoiseCanceling)	•	•		
Fully sanitizable tanks	•	•		
Intuitive drive system (ID-Intelligent Drive)	•	•		
On-board battery charger	-	optional		
Hour meter	•	•		
Battery warning light	-	•		
Battery charge level	-	•		
Automatic brush coupling and uncoupling	•	•		
Safety				
Non-marking wheels	•	•		
Squeegee with shock-resistant coupling	•	•		
(BREAK AWAY)				
Dead man's switch	•	•		

\* Eco ON/OFF system: automatically stops water flow when the machine is stationary.



TECHNICAL DATA		My50 E	Му50 В		
Squeegee width	mm	680-780	680-780		
Disc brushes Ø	(n.) mm	(1) 510 - 530 - 550	(1) 510 - 530 - 550		
Brush motor	V/W	220-230/750	24/560		
Brush rpm	rpm	135	135		
Brush pressure	kg	27,5	27,5		
Suction motor	V/W	230/450	24/310		
Type of drive	-	semi aut.	semi aut.		
Battery compartment dimensions (L x h x w)	mm	-	330 x 345 x 270		
Max gradient at full load	0/0	2%	2%		
Batteries	V/Ah C5	-	12 V/90 Ah		
Batteries weight	kg	-	54		
Machine weight (without battery)	Kg	62	62		

		cm.	<b></b>	цЦ	***	~~~~		
	Electromagnetic compatibility Emission standard	width cm	Number of brushes	Supply V/ traction	Solution tank l	Recovery tank l	Working capacity up to sq.m/h	Machine dimensions in mm L x h x w
My50 E My50 B	EN 61000-6-2, 3 EN 61000-3-2, 3	51-53-55	1	230/50 / semi aut. - /24/semi aut.	40	40	1600	1165x995x541





FIMAP spa - Via Invalidi del Lavoro, 1 - 37050 S. Maria di Zevio - Verona - It Tel. +39 045 6060411 - Fax +39 045 6060417 - E-mail: fimap@fimap.com

